

Level probe type EL041

Application and function

The level probe type EL041 serves as primary element for the following controllers

LMC2	Low water level limiter
DHR1	2-point water level controller with HWL-alarm
DLR1	2-point water level controller with LWL-alarm
DS1	LWL and HWL signaling

Technical basic equipment

Mechanical connection	G ½ (SW27)	
Electrical connection	Plug connection with screw terminals, traction relief	
Material	Probe housing	stainless steel
	Probe rod	stainless steel
	Probe extension	stainless steel
	Insulator	PTFE
	Socket	Polyamid
	Sealing ring	Soft iron

Technical data

Allowable pressure	PS	[bar]	32
Allowable temperature	TS	[° C]	239
Cable gland			M16x1,5
Protection as per DIN VDE 0470			IP65
Allowable temperature on plug			100° C

Dimension Y [mm] min. 125		
1700	with protection tube > DN80	vertical installation position
800	with protection tube DN50	vertical installation position
800	with protection tube DN50/100	inclined installation up to 45°

Addition

- If shut-off valves are mounted between the process connections of the add-on-housing and the boiler supports, an electric locking system (end switch) has to be installed.
- A drain valve is to be mounted to the add-on-housing.
- Use in mounting supports if the boiler support corresponds to the representations according to Data Sheet D-08-D-16351-0. Protective tube K, flange, screws, nuts and seals can also be supplied.
- For electrode support flange see Data Sheet D-08-D-22510-0

